



WILLEM TWEE / MAIN HALL AUDIO SPECS 2026

TECHNICAL SPECIFICATIONS

Maximum capacity	500 (standing) 150 (seated)
Maximum sound level	103 db(A) Leq over 15 minutes 120 dB(C) Leq over 15 minutes

These limits are set by Dutch law, fines may apply if limits are exceeded!

Load In/Out

Street level, a flat push of approximately 25m.
Smallest doorway: 2,0m high and 0,88m wide.

Stage

Dimensions	5,6m x 10,7m
Playing surface	5,0m x 7,6m
Clearance	3,0m (to grid)
Height	1,0m
Curtain	Black curtain at the back of the stage 3,25m x 8,0m

AUDIO SPECS

General

110V Power supply	1x Tube Amp Doctor VT500ESG-S (500VA Max)
DJ Equipment	4x Pioneer CDJ 2000 NXS2 2x Pioneer DJM 900 NXS2 1x Pioneer XDJ-RX 3x Technics SL1210
Fans	2x Showgear SF-100 ventilator

Additional audio power supply (Artist)

Stage left 1x 3 phase 32A CEE-form

Audio control

Position FOH
Console 1x Allen & Heath SQ6 (with 32 channel stage rack)PA
Mains 6x L'Acoustics ARCS
Subs 4x L'Acoustics SB218
Front fills 2x L'Acoustics 112P
Amps 4x L'Acoustics LA48a
Processing 1x ACX XP4080 DSP

Tie lines

FOH to Stage left 2x CAT 5
6x Analog Lines
Stage left to FOH 6x Analog Lines

Monitor world

Position Stage left
Console 1x Allen & Heath SQ7

Monitors

Stage wedges 6x dB Technologies FMX15

Microphones

2x AKG 214 1x Shure Beta 56a
1x AKG D112 3x Shure Beta 57a
1x AKG P170 2x Shure Beta 58
4x Devine SM-100 1x Shure Beta 87c
2x Røde M5 1x Shure Beta 91a
4x Sennheiser e604 4x Shure SM57
1x Sennheiser e904 6x Shure SM58
2x Sennheiser e906 2x Shure SLXD2 Beta 58 (Wireless)
1x Shure Beta 52a

DI's

2x BSS AR-133 Active DI

2x Klark Teknik DN100 Active DI

2x Radial Pro AV2 Passive Stereo DI

1x Radial Pro D2 Passive Stereo DI